Table 1. Selected acute and chronic ecological screening levels (Eco SLs) for chemicals in water ^a

| CONTAMINANT OF INTEREST ^b | SELECTED ACUTE SL (µg/L) | SELECTED CHRONIC SL (µg/L) | ACUTE SOURCE OR SURROGATE ^c | CHRONIC SOURCE OR SURROGATE ^C | CITATIONS AND NOTES ^d |
|---|--------------------------------|----------------------------------|---|---|--|
| Dioxins | | | | | |
| Dioxin (2,3,7,8 TCDD) | 0.01 | 0.0001 | ODEQ | AWQC | EPA (1984) |
| Dibenzofuran | 66 | 3.7 | Tier II | Tier II | |
| Metals | | | | | |
| Aluminum | 750 | 87 | AWQC | AWQC | These criteria only apply to waters within a pH range of $6.5 - 9.0$ as given in the national AWQC. |
| Antimony | 180 | 30 | Tier II | Tier II | |
| Arsenic | 340 | 150 | AWQC | AWQC | As(III) |
| Barium | 110 | 4 | Tier II | Tier II | |
| Beryllium | 35 | 0.66 | Tier II | Tier II | Per EPA comments use Tier II instead of ODEQ guidance values. |
| Butyltin ion | 0.46 | 0.072 | AWQC | AWQC | TBT value |
| Cadmium | 0.52 | 0.09 | AWQC | AWQC | Criteria are hardness-dependent. These values correspond to a hardness of 25 mg/L calcium carbonate (estimate for lower Willamette River) and were adjusted using EPA-provided equations. Criteria are for dissolved fraction. |
| Chromium (III) | 183.1 | 23.8 | AWQC | AWQC | Criteria are hardness-dependent. These values correspond to a hardness of 25 mg/L calcium carbonate (estimate for lower Willamette River) and were adjusted using EPA-provided equations. Criteria are for dissolved fraction. |
| Chromium (VI) | 16 | 11 | AWQC | AWQC | Criteria are hardness-dependent. These values correspond to a hardness of 25 mg/L calcium carbonate (estimate for lower Willamette River) and were adjusted using EPA-provided equations. Criteria are for dissolved fraction. |
| Cobalt | 1500 | 5.1 | Tier II | LCV | |

Table 1. Selected acute and chronic ecological screening levels (Eco SLs) for chemicals in water ^a

| CONTAMINANT OF INTEREST ^b | SELECTED ACUTE SL (µg/L) | SELECTED CHRONIC SL (µg/L) | ACUTE SOURCE OR SURROGATE ^C | CHRONIC SOURCE OR SURROGATE ^c | CITATIONS AND NOTES ^d |
|---|--------------------------------|----------------------------------|---|--|--|
| Copper | 3.64 | 2.74 | AWQC | AWQC | Criteria are hardness-dependent. These values correspond to a hardness of 25 mg/L calcium carbonate (estimate for lower Willamette River) and were adjusted using EPA-provided equations. Criteria are for dissolved fraction. |
| Cyanide | 22 | 5.2 | AWQC | AWQC | |
| Dibutyltin ion | 0.46 | 0.072 | AWQC | AWQC | TBT value |
| Iron | NA | 1,000 | NA | AWQC | Per EPA comments, exclude acute value. |
| Lead | 13.88 | 0.54 | AWQC | AWQC | Criteria are hardness-dependent. These values correspond to a hardness of 25 mg/L calcium carbonate (estimate for lower Willamette River) and were adjusted using EPA-provided equations. Criteria are for dissolved fraction. |
| Magnesium | 820,000 | 82,000 | LCV*10 | LCV | |
| Manganese | 2,300 | 120 | Tier II | Tier II | |
| Mercury | 1.4 | 0.77 | AWQC | AWQC | |
| Methyl-mercury | 0.099 | 0.0028 | Tier II | Tier II | |
| Nickel | 144.9 | 16.1 | AWQC | AWQC | Criteria are hardness-dependent. These values correspond to a hardness of 25 mg/L calcium carbonate (estimate for lower Willamette River) and were adjusted using EPA-provided equations. Criteria are for dissolved fraction. |
| Potassium | 530,000 | 53,000 | LCV*10 | LCV | |
| Selenium | 12.8 | 5 | AWQC | AWQC | The listed acute value is for selenate, and is the lower of the published criteria for selenate and selenite. |
| Silver | 0.3 | 0.1 | AWQC | ODEQ | AWQC are hardness-dependent. This value corresponds to a hardness of 25 mg/L calcium carbonate (estimate for lower Willamette River) and was adjusted using EPA-provided equations. Criteria are for dissolved fraction. ODEQ guidance value based on old AWQC (EPA 1980). |
| Sodium | 6,800,000 | 680,000 | LCV*10 | LCV | |
| Thallium | 1,400 | 40 | ODEQ | ODEQ | |
| Tributyltin ion | 0.46 | 0.072 | AWQC | AWQC | Criteria apply to TBT ion concentration (EPA 2003a) |

Table 1. Selected acute and chronic ecological screening levels (Eco SLs) for chemicals in water ^a

| CONTAMINANT OF INTEREST ^b | SELECTED ACUTE SL (µg/L) | SELECTED CHRONIC SL (µg/L) | ACUTE SOURCE OR SURROGATE ^c | CHRONIC SOURCE OR SURROGATE ^c | CITATIONS AND NOTES ^d |
|---|--------------------------|----------------------------------|---|--|--|
| Vanadium | 280 | 20 | Tier II | Tier II | |
| Zinc | 36.2 | 36.5 | AWQC | AWQC | Criteria are hardness-dependent. These values correspond to a hardness of 25 mg/L calcium carbonate (estimate for lower Willamette River) and were adjusted using EPA-provided equations. Criteria are for dissolved fraction. |
| PAHs | | | | | |
| 2-Methylnaphthalene | 37 | 2.1 | Tier II | Tier II | The acute and chronic SLs are for the surrogate compound 1-methynapthalene. |
| Acenaphthene | 80 | 23 | Tier II | Tier II | The listed acute and chronic SLs are the EPA calculated FAV and FCV for sediment quality guideline development. |
| Acenaphthylene | 80 | 306.9 | acenaphthene | EPA (2003b) PAH mixtures | |
| Anthracene | 13 | 0.73 | Tier II | Tier II | The document calculated for AWQC, but never adopted. |
| Benzo(a)anthracene | 0.49 | 0.027 | Tier II | Tier II | |
| Benzo(a)pyrene | 0.24 | 0.014 | Tier II | Tier II | |
| Benzo(b)fluoranthene | NA | 0.6774 | NA | EPA (2003b) PAH mixtures | Per EPA, exclude the acute SL. |
| Benzo(b+j)fluoranthene | NA | 0.6415 | NA | benzo(k)fluoranthene | Per EPA, exclude the acute SL |
| Benzo(b+k)fluoranthene | NA | 0.6415 | NA | benzo(k)fluoranthene | Per EPA, exclude the acute SL |
| Benzo(g,h,i)perylene | NA | 0.4391 | NA | EPA (2003b) PAH mixtures | Per EPA, exclude the acute SL |
| Benzo(k)fluoranthene | NA | 0.6415 | NA | EPA (2003b) PAH mixtures | Per EPA, exclude the acute SL |
| Chrysene | NA | 2.042 | NA | EPA (2003b) PAH mixtures | Per EPA, exclude the acute SL |
| Dibenz(a,h)anthracene | 0.24 | 0.2825 | benzo(a)pyrene | EPA (2003b) PAH mixtures | |
| Fluoranthene | 33.6 | 6.16 | AWQC | AWQC | Presented in Suter and Tsao (1996) (Tier II), calculated for AWQC though never adopted. |

Table 1. Selected acute and chronic ecological screening levels (Eco SLs) for chemicals in water ^a

| CONTAMINANT OF INTEREST ^b | SELECTED ACUTE SL (µg/L) | SELECTED CHRONIC SL (µg/L) | ACUTE SOURCE OR SURROGATE ^C | CHRONIC SOURCE OR SURROGATE ^c | CITATIONS AND NOTES ^d |
|---|--------------------------------|----------------------------------|---|--|---|
| Fluorene | 70 | 3.9 | Tier II | Tier II | |
| Indeno(1,2,3-cd)pyrene | 0.24 | 0.275 | benzo(a)pyrene | EPA (2003b) PAH mixtures | |
| Naphthalene | 190 | 12 | Tier II | Tier II | |
| Phenanthrene | 30 | 6.3 | AWQC | AWQC | Presented in Suter and Tsao (1996) (Tier II), calculated for AWQC though never adopted. |
| Pyrene | NA | 10.11 | NA | EPA (2003b) PAH mixtures | Per EPA, exclude the acute SL. |
| PCBs | | | | | |
| Aroclor 1221 | 5 | 0.28 | Tier II | Tier II | |
| Aroclor 1242 | 1.2 | 0.053 | Tier II | Tier II | |
| Aroclor 1248 | 1.4 | 0.081 | Tier II | Tier II | |
| Aroclor 1254 | 0.6 | 0.033 | Tier II | Tier II | |
| Aroclor 1260 | 1,700 | 94 | Tier II | Tier II | |
| Total PCBs | 2 | 0.014 | ODEQ | Tier II | ODEQ value same as value presented in Suter and Tsao (1996) (Tier II), calculated for AWQC though never adopted. Total PCBs criterion applies to total PCBs, as either sum of all homologs, Aroclors, or congeners. |
| Pesticides | | | | | |
| 2,4' D | 800 | 4 | LC50/2 | MacDonald ES (1999), Ontario Water Quality objective | ECOTOX per EPA |
| 2,4'-DDD | 1.1 | 0.001 | 4,4'-DDT | 4,4'-DDT | EPA (2006) National Recommended Water Quality Criteria |
| 2,4'-DDE | 1.1 | 0.001 | 4,4'-DDT | 4,4'-DDT | EPA (2006) National Recommended Water Quality Criteria |
| 2,4'-DDT | 1.1 | 0.001 | 4,4'-DDT | 4,4'-DDT | EPA (2006) National Recommended Water Quality Criteria |
| 4,4'-DDD | 1.1 | 0.001 | 4,4'-DDT | 4,4'-DDT | EPA (2006) National Recommended Water Quality Criteria |
| 4,4'-DDE | 1.1 | 0.001 | 4,4'-DDT | 4,4'-DDT | EPA (2006) National Recommended Water Quality Criteria |
| 4,4'-DDT | 1.1 | 0.001 | AWQC | AWQC | These criteria apply to 4,4'-DDT and its metabolites as stated in Footnote ii of EPA (2006) AWQC. |

Table 1. Selected acute and chronic ecological screening levels (Eco SLs) for chemicals in water ^a

| CONTAMINANT OF INTEREST ^b | SELECTED ACUTE SL (µg/L) | SELECTED CHRONIC SL (µg/L) | ACUTE SOURCE OR SURROGATE ^c | CHRONIC SOURCE OR SURROGATE ^C | CITATIONS AND NOTES ^d |
|--|--------------------------------|----------------------------------|---|---|---|
| Aldrin | 3 | 0.3 | AWQC | MacDonald ES (1999) | Acute AWQC were developed using previous guidelines (prior to 1985) and were calculated differently than other AWQC. |
| alpha-Endosulfan | 0.22 | 0.056 | AWQC | AWQC | Criteria were derived from data for endosulfan and are most appropriately applied to sum of alpha- and beta-endosulfan but can be applied to either, individually. Acute AWQC were developed using previous guidelines (prior to 1985) and were calculated differently than other AWQC. |
| alpha- Hexachlorocyclohexane | 0.95 | 0.08 | gamma- hexachlorocyclohexane | gamma- hexachlorocyclohexane | |
| beta-Endosulfan | 0.22 | 0.056 | AWQC | AWQC | |
| beta- Hexachlorocyclohexane | 0.95 | 0.08 | gamma- Hexachlorocyclohexane | gamma- Hexachlorocyclohexane | |
| Carbazole | 465 | 18.6 | LC50/2 | LC50/50 | Brooke (1991) as presented in ECOTOX |
| Chlordane | 1.2 | 0.0043 | AWQC/2 | AWQC | Acute AWQC were developed using previous guidelines (prior to 1985) and were calculated differently than other AWQC and are divided by 2 so it is comparable to other AWQC values. |
| cis-Chlordane | 2.4 | 0.0043 | sum chlordane | per EPA | |
| cis-Nonachlor | 1.2 | 0.0043 | sum chlordane | sum chlordane | |
| Dalapon | NA | 2 | NA | literature | George et al. (1982) |
| delta- Hexachlorocyclohexane ^e | 0.95 | 0.08 | Lindane | Lindane | Per EPA, use lindane as a surrogate. |
| Dichloroprop | 250 | 10 | LC50/2 | LC50/50 | EPA (2000) |
| Dieldrin | 0.24 | 0.056 | AWQC | AWQC | |
| Endosulfan sulfate | 0.22 | 0.056 | alpha or beta endosulfan AWQC | alpha or beta endosulfan AWQC | |
| Endrin | 0.086 | 0.036 | AWQC | AWQC | |
| Endrin aldehyde | 0.086 | 0.036 | endrin | endrin | |
| Endrin ketone | 0.086 | 0.036 | endrin | endrin | |

Table 1. Selected acute and chronic ecological screening levels (Eco SLs) for chemicals in water ^a

| CONTAMINANT OF INTEREST ^b | SELECTED ACUTE SL (µg/L) | SELECTED CHRONIC SL (µg/L) | ACUTE SOURCE OR SURROGATE ^c | CHRONIC SOURCE OR SURROGATE ^c | CITATIONS AND NOTES ^d |
|---|--------------------------------|----------------------------------|---|--|--|
| gamma- Hexachlorocyclohexane | 0.95 | 0.08 | AWQC | ODEQ | |
| Heptachlor epoxide | 0.26 | 0.0038 | AWQC/2 | AWQC | Derived from data for heptachlor but may also be applied to heptachlor epoxide. Acute AWQC were developed using previous guidelines (prior to 1985) and were calculated differently than other AWQC and are divided by 2 to make the value comparable to other AWQC values. |
| Heptachlor | 0.26 | 0.0038 | AWQC/2 | AWQC | Acute AWQC were developed using previous guidelines (prior to 1985) and were, therefore, calculated differently than other AWQC and are divided by 2 to make the value comparable to other AWQC values. |
| Methoxychlor | 0.3 | 0.03 | AWQC*10 | AWQC | |
| Oxychlordane | 1.2 | 0.0443 | Chlordane | Chlordane | Per EPA, chlordane is used as a surrogate. |
| Retene | 176.5 | 100 | LC50/2 | literature value | Billiard (1999) |
| Silvex | 125 | 5.0 | LC50/2 | LC50/50 | ECOTOX per EPA |
| Total DDT | 1.1 | 0.001 | AWQC | AWQC | AWQC for 4,4'-DDT applies to total DDTs. Acute AWQC were developed using previous guidelines (prior to 1985) and were calculated differently than other AWQC. |
| ТРН | | | | | |
| Diesel ^f | NA | NA | NA | EPA | EPA comment 3.1.4. The value is not applied pending further technical justification from EPA as the proposed value (0.014 ug/l) is a narrative water quality number and does not meet the data acceptability criteria of a chronic endpoint based on survival, growth, reproduction. |
| Gasoline ^f | NA | NA | NA | EPA | EPA comment 3.1.4. The value is not applied pending further technical justification from EPA as the proposed value (114 ug/l) is a narrative water quality number and does not meet the data acceptability criteria of a chronic endpoint based on survival, growth, reproduction. |
| Phenols | | | | | |
| 2,4-Dimethylphenol | 2120 | 42.4 | ODEQ | Acute value/50 | |

Table 1. Selected acute and chronic ecological screening levels (Eco SLs) for chemicals in water ^a

| CONTAMINANT OF INTEREST ^b | SELECTED ACUTE SL (µg/L) | SELECTED CHRONIC SL (µg/L) | ACUTE SOURCE OR SURROGATE ^c | CHRONIC SOURCE OR SURROGATE ^c | CITATIONS AND NOTES ^d |
|---|--------------------------|----------------------------------|---|--|---|
| 2-Chlorophenol | 4380 | 2000 | ODEQ | ODEQ | |
| 2-Methylphenol | 230 | 13 | Tier II | Tier II | |
| 3- and 4-methylphenol coelution | 230 | 13 | 2-methylphenol | 2-methylphenol | |
| Pentachlorophenol | 10.7 | 8.2 | AWQC | AWQC | The PCP criterion is pH dependent. The listed SLs were calculated for waters at a pH = 7.2 and will vary with the pH of the water column. |
| Phenol | 3600 | 110 | Tier II | Tier II | Presented in Suter and Tsao (1996) (Tier II), calculated for AWQC though never adopted. |
| Phthlates | | | | | |
| Bis(2-ethylhexyl) phthalate | 27 | 3 | Tier II | Tier II | |
| Butylbenzyl phthalate | 150 | 3 | Tier II*50 | bis(2-ethylhexyl) phthalate | Per EPA, apply bis(2-ethylhexyl) phthalate value of 3 and a safety factor of 50 to calculate the acute value. |
| Dibutyl phthalate | 150 | 3 | Tier II*50 | bis(2-ethylhexyl) phthalate | Per EPA, apply bis(2-ethylhexyl) phthalate value of 3 and a safety factor of 50 to calculate the acute value. |
| Diethyl phthalate | 150 | 3 | Tier II*50 | bis(2-ethylhexyl) phthalate | Per EPA, apply bis(2-ethylhexyl) phthalate value of 3 and a safety factor of 50 to calculate the acute value. |
| Dimethyl phthalate | 150 | 3 | Tier II*50 | bis(2-ethylhexyl) phthalate | Per EPA, apply bis(2-ethylhexyl) phthalate value of 3 and a safety factor of 50 to calculate the acute value. |
| Di-n-octyl phthalate | 150 | 3 | Tier II*50 | bis(2-ethylhexyl) phthalate | Per EPA, apply bis(2-ethylhexyl) phthalate value of 3 and a safety factor of 50 to calculate the acute value. |
| SVOCs | | | | | |
| Benzoic acid | 740 | 42 | Tier II | Tier II | |
| Hexachlorobenzene | 6.0 | 3.68 | EPA | MacDonald ES (1999) | EPA draft criterion |
| Hexachlorobutadiene | 90 | 9.3 | ODEQ | ODEQ | |
| VOCs | | | | | |
| 1,1,1-Trichloroethane | 200 | 11 | Tier II | Tier II | |

Table 1. Selected acute and chronic ecological screening levels (Eco SLs) for chemicals in water ^a

| CONTAMINANT OF INTEREST ^b | SELECTED ACUTE SL (µg/L) | SELECTED CHRONIC SL (µg/L) | ACUTE SOURCE OR SURROGATE ^c | CHRONIC SOURCE OR SURROGATE ^c | CITATIONS AND NOTES ^d |
|---|--------------------------------|----------------------------------|---|---|--|
| 1,1,2,2- Tetrachloroethane | 2,100 | 610 | Tier II | Tier II | EPA direction to use the Tier II acute value, instead of the ODEQ acute value. |
| 1,1,2-Trichloroethane | 18,000 | 9,400 | ODEQ | ODEQ | |
| 1,1-Dichloroethane | 830 | 47 | Tier II | Tier II | 1,2-dichloroethene screening values apply to both cis- and transcongeners. |
| 1,1-Dichloroethene (1,1-Dichloroethylene) | 450 | 25 | Tier II | Tier II | |
| 1,2,3-Trichloropropane | 2,050 | 82 | LC50/2 | LC50/50 | Kielhorn et al. (2003) |
| 1,2,4-Trimethylbenzene | 130 | 7.3 | ethylbenzene | ethylbenzene | |
| 1,2-Dichlorobenzene | 260 | 14 | Tier II | Tier II | |
| 1,2-Dichloroethane | 8,800 | 910 | Tier II | Tier II | |
| 1,2-Dichloroethene (trans) | 1,100 | 590 | Tier II | Tier II | |
| 1,2-Dichloropropane | 23,000 | 5,700 | ODEQ | ODEQ | |
| 1,3,5-Trimethylbenzene | 130 | 7.3 | ethylbenzene | ethylbenzene | |
| 1,3-Dichlorobenzene | 630 | 71 | Tier II | Tier II | |
| 1,4-Dichlorobenzene | 180 | 15 | Tier II | Tier II | |
| 1,4-Dioxane | 900,000 | 36,000 | LC50/2 | LC50/50 | Brooke (1987), screening values are based on a measured LC50 for the amphipod <i>Gammarus pseudolimnaeus</i> . |
| 2-Hexanone (me-butyl ketone) | 1,800 | 99 | Tier II | Tier II | |
| 4-chloro-3-methylphenol | 30 | 0.60 | ODEQ | ODEQ/50 | |
| Acetone | 28,000 | 1,500 | Tier II | Tier II | |
| Acrolein | 68 | 21 | ODEQ | ODEQ | |
| Ammonia | 19,727 | 5,389 | AWQC | AWQC | Ammonia was not analyzed in surface water or transition zone water. |
| Benzene | 2,300 | 130 | Tier II | Tier II | |

Table 1. Selected acute and chronic ecological screening levels (Eco SLs) for chemicals in water ^a

| CONTAMINANT OF INTEREST ^b | SELECTED ACUTE SL (µg/L) | SELECTED CHRONIC SL (µg/L) | ACUTE SOURCE OR SURROGATE ^c | CHRONIC SOURCE OR SURROGATE ^c | CITATIONS AND NOTES ^d |
|--|--------------------------------|----------------------------------|---|--|---|
| Bis(2-ethylhexyl)adipate | 240 | 24 | LC50/2 | Felder et al. (1986); Daphnia chronic value | MATC value; used lower end of range 24-52 ug/L |
| Bromochloromethane | 11,000 | 220 | ODEQ | ODEQ/50 | ODEQ criteria for halomethanes. |
| Bromodichloromethane | 11,000 | 220 | ODEQ | ODEQ/50 | ODEQ criteria for halomethanes. |
| Bromomethane | 11,000 | 220 | ODEQ | ODEQ/50 | ODEQ criteria for halomethanes. |
| Carbon disulfide | 17 | 0.92 | Tier II | Tier II | |
| Chlorobenzene | 250 | 50 | ODEQ | ODEQ | The screening values are for chlorobenzenes, not chlorobenzene (i.e. monochlorobenzene) specifically. |
| Chloroethane | 830 | 47 | 1,1-dichloroethane, Tier II | 1,1-dichloroethane, Tier II | |
| Chloroform | 28,900 | 1,240 | ODEQ | ODEQ | |
| Chloromethane | 11,000 | 220 | ODEQ | ODEQ/50 | The acute value is based on ODEQ acute criterion for halomethanes. |
| cis-1,2-Dichloroethene (cis-1,2- Dichloroethylene) | 11,600 | 590 | ODEQ | Tier II | |
| Dichlorodifluoromethane | 11,000 | 90 | ODEQ | Canadian EQG | ODEQ criteria for halomethanes. |
| Ethylbenzene | 3200 | 7.3 | ODEQ | Tier II | |
| Hexachloroethane | 210 | 12 | Tier II | Tier II | |
| Isophorone | 117,000 | 130 | ODEQ | MacDonald ES (1999) | |
| Isopropylbenzene (1- Methylethylbenzene) | 130 | 7.3 | ethylbenzene | ethylbenzene | |
| m,p-Xylene (m-xylene) | 1,200 | 66.67 | EPA | EPA | EPA (2006a) |
| m,p-Xylene (p-xylene) | 230 | 13 | xylene | Xylene | |
| Methyl isobutyl ketone | 2,200 | 170 | Tier II | Tier II | A commonly used synonym for MIBK is 4-methyl-2-pentanone. |
| Methylene bromide | 11,000 | 11 | ODEQ | MacDonald ES (1999) | The acute value is based on ODEQ acute criterion for halomethanes. |
| Methylene chloride | 11,000 | 2,200 | ODEQ | Tier II | The acute value is based on ODEQ acute criterion for halomethanes. |

Table 1. Selected acute and chronic ecological screening levels (Eco SLs) for chemicals in water ^a

| CONTAMINANT OF INTEREST ^b | SELECTED ACUTE SL (µg/L) | SELECTED CHRONIC SL (µg/L) | ACUTE SOURCE OR SURROGATE ^c | CHRONIC SOURCE OR SURROGATE ^c | CITATIONS AND NOTES ^d |
|---|--------------------------------|----------------------------------|---|---|---|
| Methylethyl ketone | 240,000 | 14,000 | Tier II | Tier II | |
| MTBE | 151,000 | 10,000 | Mancini et al. (2002) | Canadian EQG | |
| n-Butylbenzene | 130 | 7.3 | ethylbenzene | ethylbenzene | |
| n-Propylbenzene | 130 | 7.3 | ethylbenzene | ethylbenzene | |
| o-Xylene | 230 | 13 | xylene | Xylene | |
| Perchlorate | NA | 18 | NA | Goleman et al. (2002) | |
| p-Isopropyltoluene (p-cymene) | 17,500 | 9.8 | toluene | toluene | |
| Sec-butylbenzene | 130 | 7.3 | ethylbenzene | ethylbenzene | |
| Styrene | NA | 4 | NA | MacDonald ES (1999) | |
| tert-Butylbenzene | 130 | 7.3 | ethylbenzene | ethylbenzene | |
| Tetrachloroethene | 5,280 | 840 | ODEQ | ODEQ | |
| Toluene | 17,500 | 9.8 | ODEQ | Tier II | |
| trans-1,2-Dichloroethene | 11,600 | 590 | ODEQ | Tier II | |
| Trichloroethene | 45,000 | 21,900 | ODEQ | ODEQ | |
| Trichlorofluoromethane | 11,000 | 580 | ODEQ | MacDonald ES (1999) | Acute from ODEQ criteria for halomethanes. |
| Vinyl acetate | 280 | 16 | Tier II | Tier II | |
| Vinyl chloride | 97,000 | 3,880 | NR LETH/4 | LC50/50 | Brown et al. (1977); NR LETH/4 notation represents the 10-day LC_{100} for northern pike divided by four. |
| Vinylidene chloride | 11,600 | 25 | ODEQ | Tier II | |
| Xylene | 230 | 13 | Tier II | Tier II | |

The process for developing these screening levels is presented in a technical memo (Windward 2005). As recommended by EPA, these screening levels are intended to be part of a tool that is "easy to use, fast, and conservative" (EPA 2005). As such, these are conservative screening values and will be taken into context through the risk process (evaluation of derivation of SL, background, etc). Water SLs will be used to evaluate surface water and transition zone water. Other water data (e.g. seep water) may be evaluated using water SLs as agreed upon between LWG, EPA, and EPA's partners.

b Contaminants of interest included detected chemicals from water samples from Round 2 data collection (including surface water and transition zone water) except nutrients, petroleum products (heavy oil and motor oil), and PCB congeners (dioxin-like congeners will be included in dioxin value).

Portland Harbor RI/FS

LWG
Lower Willamette Group

Ecological Screening Levels in Water REVISED DRAFT October 13, 2006

- Ambient Water Quality Criteria (AWQC) are from EPA (2002) and EPA(2006b). Tier II and lowest chronic values (LCV) are from Suter and Tsao (1996). Oregon Department of Environmental Quality (ODEQ) values are from ODEQ (2001). PAH mixture values are from EPA (2003b). Canadian EQG are from Canadian Water Quality Guidelines updated 2005. MacDonald ES (1999) are from Environment Canada, Georgia Basin Action Plan compendium of environmental quality benchmarks.
- d References cited from ECOTOX and primary literature.
- An acute screening value for delta-hexachlorocyclohexane exists from MacDonald ES (1999), the proposed EPA value was applied, but requires more technical explanation for using a lindane surrogate number.
- The proposed EPA chronic value for gasoline and diesel range hydrocarbons (0.014 ug/L) is not applied pending further technical justification from EPA. The proposed EPA number is a narrative water quality criteria and does not meet data acceptability standards of a chronic toxicity endpoint of growth, reproduction, or mortality.

Ecological Screening Levels in Water
REVISED DRAFT
October 13, 2006

REFERENCES

Billiard SM, Querbach K, Hodson PV. 1999. Toxicity of retene to early life stages of two freshwater fish species. Environ Toxicol Chem 18(9):2070-2077.

Brooke L. 1987. Report of the flow-through and static acute text comparisons with fathead minnows and acute tests with an amphipod and a cladoceran. Center for Lake Superior Environmental Studies, University of Wisconsin-Superior, Superior, WI.

Brooke LT. 1991. Results of freshwater exposures with the chemicals atrazine, biphenyl, butachlor, carbaryl, carbazole, dibenzofuran, 3,3'-dichlorobenzidine, dichlorvos 1,2-epoxyethylbenzene (styrene oxide), isophorone, isopropalin, oxyc. Center for Lake Superior Environmental Studies, University of Wisconsin-Superior, Superior, WI.

Brown ER, Sinclair T, Keith L, Beamer P, Hazdra JJ, Nair V, Callaghan O. 1977. Chemical pollutants in relation to diseases in fish. Ann NY Acad Sci 298:535-546.

EPA. 1984. Ambient water quality criteria for 2,3,7,8-tetrachlorodibenzo-p-dioxin. EPA 440/5-84-007. US Environmental Protection Agency, Washington, DC.

EPA. 2000. Pesticide Ecotoxicity Database (formerly Environmental Effects Database, EEDB) [online]. Office of Pesticide Programs, US Environmental Protection Agency, Washington, D C. Available from.

EPA. 2002. National recommended water quality criteria: 2002. EPA-822-R-02-047. US Environmental Protection Agency, Washington, DC.

EPA. 2003a. Ambient aquatic life water quality criteria for tributyltin (TBT) - final. EPA 822-R-03-031. US Environmental Protection Agency, Washington, DC.

EPA. 2003b. Procedures for the derivation of equilibrium partitioning sediment benchmarks (ESBs) for the protection of benthic organisms: PAH mixtures. EPA-600-R-02-013. Office of Research and Development, US Environmental Protection Agency, Washington, DC.

EPA. 2005. Exposure assessment tools and models: screening level tools [online]. Office of Pollution Prevention and Toxics, US Environmental Protection Agency, Washington, DC. Updated 5/24/04. [Cited 8/25/05]. Available from: http://www.epa.gov/opptintr/exposure/docs/screen.htm.

EPA. 2006a. Memorandum from D. Mount to ERAF tri-chairs (B. Pluta, M. Sprenger, V. Madden) dated September 13, 2006: Error in prior calculation of GLI Tier II SCV for m-xylene. National Health and Environmental Effects Research Laboratory, US Environmental Protection Agency, Duluth, MN.

EPA. 2006b. National recommended water quality criteria (4304T). US Environmental Protection Agency, Washington, DC.

Felder JD, Adams WH, Saeger VW. 1986. Assessment of the safety of dioctyl adipate in freshwater environments. Environ Toxicol Chem 5(8):777-784.

George JP, Hingorani HG, Rao KS. 1982. Herbicide toxicity to fish-food organisms. Environ Pollut Series A Ecol Biol 28(3):183-188.

Ecological Screening Levels in Water
REVISED DRAFT
October 13, 2006

Goleman WL, Urquidi LJ, Anderson TA, Smith EE, Kendall RJ, Carr JA. 2002. Environmentally relevant concentrations of ammonium perchlorate inhibit development and metamorphosis in *Xenopus laevis*. Environ Toxicol Chem 21(2):424-430.

Kielhorn J, Koennecker G, Pohlenz-Michel C, Schmidt S, Mangelsdorf I. 2003. Concise international chemical assessment (CICAD) document 56: 1,2,3-trichloropropane [online]. World Health Organization, Geneva. Available from: http://www.inchem.org/documents/cicads/cicads/cicads6.htm.

MacDonald ES. 1999. Appendix 2-4: A summary of the available water quality criteria and guidelines for the protection of freshwater aquatic life. In: The Georgia Basin action plan: A compendium of environmental quality benchmarks. Prepared for Environment Canada. MacDonald Environmental Services Ltd, Ladysmith, BC.

Mancini ER, Steen A, Rausina GA, Wong DCL, Arnold WR, Gostomski FE, Davies TT, Hockett JR, Stubblefield WA, Drottar KR, Springer TA, Errico P. 2002. MTBE ambient water quality criteria development: a public/private partnership. Environ Sci Tech 36:125-129.

ODEQ. 2001. Water pollution, Division 41, State-wide water quality management plan; beneficial uses, policies, standards, and treatment criteria for Oregon. 340-041-0001. [online]. Oregon Department of Environmental Quality, Portland, OR. Available from: http://www.deq.state.or.us/wq/wqrules/340Div41.pdf.

Suter GW, Tsao CL. 1996. Toxicological benchmarks for screening potential contaminants of concern for effects on aquatic biota: 1996 revision. Prepared for U.S. Department of Energy Office of Environmental Management. Risk Assessment Program, Health Sciences Research Division.

Windward. 2005. Portland Harbor RI/FS. Ecological risk assessment: Process for selecting acute and chronic water screening levels for Portland Harbor surface water, groundwater, and transition zone water. WE-05-0004. Draft. Prepared for Lower Willamette Group. Windward Environmental LLC, Seattle, WA.